

## SYN P9000

FULLY SYN PREMIUM  
ENGINE OILS WITH ESTER

**MaxPro1 SYN P9000** is a series of fully synthetic engine oil formulated with ester. It is designed for passenger cars, light trucks and high-performance vehicles. These state-of-the-art engine oils are recommended for year-round service in modern engines operating at higher temperatures and speeds. They provide excellent wear protection and friction reduction across a wide range of operating conditions.


**MaxPro1 SYN P9000** should be used in engines where superior performance and maximum protection are demanded. They easily surpass the performance requirements of API SN/CF standards.



### APPLICATIONS

**MaxPro1 SYN P9000** series of multi-grade engine oils are recommended for passenger cars, vans, light-duty trucks and sports utility vehicles.

**MaxPro1 SYN P9000** SAE 5W-30 and SAE 5W-40 grades are especially recommended for vehicles with modern aftertreatment devices.



### FEATURES AND BENEFITS

- Excellent protection of engines and emission devices
- High detergency provides improved engine cleanliness
- Excellent shear stability for consistent performance
- Low volatility reduces oil consumption in severe service
- Superior thermal stability ensures extended service intervals
- Synthetic components provide durable oil film in bearings and cams
- Outstanding flow characteristics even in low ambient temperatures thus minimizing wear and damages during cold starts
- Excellent anti-corrosion and anti-rust properties
- Prolongs engine life and improves running efficiency
- All grades are completely compatible with other conventional and synthetic engine oils



**EELQMS**  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

### PERFORMANCE LEVEL

**MaxPro1 SYN P9000** engine oils meet the following performance requirements:

Revision 11/06/19  
Superceding issue of  
19/07/18

## SYN P9000

FULLY SYN PREMIUM  
ENGINE OILS WITH ESTER

SAE 5W-30	SAE 5W-40	SAE 5W-50
API SN/SM/CF	API SN/SM/CF	API SN/SM/CF
ACEA C3	ACEA C3	-
BMW Longlife-04	BMW Longlife-04	-
-	Ford WSS-M2C917-A	-
GM dexos 2	GM dexos 2	-
MB-Approval 229.31/229.51	MB-Approval 229.31/229.51	-
-	Porsche A40	-
Renault RN0700/RN0710	Renault RN0700/RN0710	-
VW 502 00/505 00	VW 502 00/505 00/ 505 01	-



### TYPICAL PROPERTIES

SAE Grade	Test Method	5W-30	5W-40	5W-50
Product Code		<b>1105</b>	<b>1106</b>	<b>1107</b>
Appearance	Visual	Clear	Clear	Clear
Colour ASTM	ASTM D1500	<3.0	<3.0	<3.0
Density @ 15°C, kg/l	ASTM D4052	0.855	0.856	0.859
Kinematic Viscosity, cSt	ASTM D445			
@ 40°C		63.8	90.9	119.0
@ 100°C		11.1	14.6	18.1
Viscosity Index	ASTM D2270	168	168	170
CCS @ -30°C, cP	ASTM D5293	5010	5580	6050
Flash Point COC, °C	ASTM D92	228	230	236
Pour Point, °C	ASTM D97	-36	-36	-33
TBN, mg KOH/g	ASTM D2896	8	8	8

### AVAILABLE SIZE AND PART NUMBER

	4L	200L
SYN P9000 SAE 5W-30	1105-04	1105-200
SYN P9000 SAE 5W-40	1106-04	1106-200
SYN P9000 SAE 5W-50	1107-04	1107-200



**EELQMS**

EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

Revision 11/06/19  
Superceding issue of  
19/07/18